

# Designing an E-shaped Microstrip Patch Antenna for Ultra-wide Band Application using Line Feeding

Venkateswara Reddy V\*, Pradeep M. Hadalgi

Department of Applied Electronics Gulbarga University, Kalaburagi, Karnataka, INDIA

## ABSTRACT

This paper presents the plan and reenactment of the super wideband working recurrence Eshape microband receiving wire for different remote applications. This receiving wire will give the vital broadband in different applications like remote detecting, biomedical applications, portable radio satellites, remote correspondences, and then some. This receiving wire structure gives a usable recurrence scope of 3.14-10.6 GHz, making the radio wire appropriate for the super wideband. The performance of the designed antenna was analysed in terms of gain, return loss, VSWR, Axial Ratio, Conjugate Matching Factor, Antenna Efficiency, Current Distribution, Impedance of Antenna, Radiation Pattern. The proposed receiving wire is planned utilizing a polyimide substrate with a substrate tallness of 1.6 mm. Axial ratio is less than 0 dB. For the frequency zero GHz the Conjugate Matching Factor is -forty-five dB, for the frequency four.6 GHz the Conjugate Matching Factor is zero dB and for the frequency five GHz the Conjugate Matching Factor is -five Db. For the frequency of 4.6 GHz with a return loss of -24dB. The smith chart of E Patch Antenna is  $5.253 + j55\Omega$ , The radiation efficiency at the frequency 5.65GHz is 88 per cent. The Antenna Efficiency for the frequency 4.5 GHz is 80%.

**Keywords:** E-shaped patch antenna, IE3D, Micro-strip antenna, Radiation pattern, Return loss, VSWR.

*SAMRIDDHI : A Journal of Physical Sciences, Engineering and Technology* (2022); DOI: 10.18090/samriddhi.v14i01.12

## INTRODUCTION

The concept of the Microstrip antenna was first shown by Hertz in 1886 and applied by Marconi in 1901 and is usually presented with confirmation<sup>[1]</sup> in 1953. HUEL and Tunisia are the primary practical antenna in 1970. For the primary time since then, large-scale search and development of the microstrip antenna, which benefits those benefits, like low weight, low volume, low cost, compatible configuration, microcircuit compatibility, Mechanical stability, on solid surfaces, DEVAL and three levels of frequency regulation of active functions, absorbs many researchers to look in several ways with patch antenna and even many diverse applications.<sup>[3]</sup>

Generally, the overall microstrip antenna because the "print- ing antenna", the initial setting of the microstrip antenna also can be mentioned during a metal and penetrating insulating platform. The patch antenna is often an outsized building in wireless communications and global GPS.<sup>[4]</sup> The long- term trend is within the design of compressed devices.<sup>[6]</sup> Microstrip antenna for various techniques want to overcome this problem, like increasing the thickness of the substrate and placing parasitic elements I.W. Or configured color or stack, or change an equivalent correction<sup>[9]</sup> documented.

The patch formulation includes an electronic correction antenna.<sup>[10]</sup> These proposed systems provide an outsized

**Corresponding Author:** Venkateswara Reddy V, Department of Applied Electronics Gulbarga University, Kalaburagi, Karnataka, INDIA , e-mail: vvreddy6@gmail.com

**How to cite this article:** Reddy, V.V., & Hadalgi, P.M. (2022). Designing an E-shaped Microstrip Patch Antenna for Ultra-wide Band Application using Line Feeding. *SAMRIDDHI : A Journal of Physical Sciences, Engineering and Technology*, 14(1), 72-78.

**Source of support:** Nil

**Conflict of interest:** None

screen compared to a different research system. There are many techniques that are wont to overcome the difficulty, like increasing the thickness of the substrate, which enters parasitic components, configure this coplanar and stack or set the patch shape that has an electronic patch plan or correction of the Fathi U antenna.<sup>[20]</sup> B shapes are much easier to create length and screen and only position. the primary goal of an electronic micrometer correction antenna design is improved design programs to scale back the bandwidth.<sup>[22]</sup> The Mi- crostrip antenna configuration shows an electronic form<sup>[23]</sup> in Figure 1 and Figure 2 at an equivalent time. The Figure1 shows Geometry of Unequal E Shaped Patch Antenna. The Figure 2 represents Line-fed E-shaped patch antenna configuration.




Figure 1: Geometry of Unequal E Shaped Patch Antenna

## LITERATURE SURVEY

Ros Marie C Cleetus. *et. al.*<sup>[1]</sup> In general, microstrip antennas are also mentioned as "printed antennas", and therefore the main configuration of a microstrip antenna is often a bit of metal printed on a skinny layer of insulation. Microstrip patch antennas are often one among the foremost important starting points for wireless communication and GPS.<sup>[4]</sup> The longer-term trend is within the design of communication with embedded devices.<sup>[6]</sup> Antenna microstrip patching has been documented for several techniques that are wont to overcome this problem, such as: The patch shape correction involves the planning of an E-shaped patch antenna.<sup>[10]</sup> These proposed systems offer an outsized bandwidth range compared to the program on the opposite hand.

Numerous techniques are wont to overcome this problem, such as]. It's much easier to form an E shape just by adjusting the length, width, and site of the gaps. the most purpose of designing an E-shaped microstrip patch antenna is to upgrade the low design to urge more bandwidth.<sup>[22]</sup> The configuration of the E-shaped microstrip antenna<sup>[10]</sup> is additionally shown within the figure1 and figure2 QADDI Mohamed Hamza. *et al.*<sup>[2]</sup> This text shows a hard and fast wireless cable for ultra- wideband applications. The proposed radio wire was mounted on an FR4 miniature substrate measuring  $20 \times 30 \times 1.6$  mm<sup>3</sup> with a relative dielectric constant 4.3. The receiver cable covers the frequency range of three 1-7.5 GHz and its reflection is reduced to 55 dB,




Figure 2: Line-fed E-shaped patch antenna configuration.

i.e., a positive 5.9 dB. Provides accurate data from reflection results and reflex zone estimates. to chop off the degree effect, consider the rotation of the surface flow. a good consistency is achieved in coordination with the brand within the range. Use CST Microwave Studio for fun. The proposed wide receiver is widely used for UWB applications and other radio correspondence frames.

Yuehe Ge. *et al.*<sup>[3]</sup> sent the broadband repair receiver E (ESPA), which works within the frequency range of 5-6 GHz, in order that the top of the radio cable is not any thicker than the cardboard shown. Also, for a change, two unique sets of radio cables are shown up close. Introducing the ESPA launch for alternative microstrip activities which will be easily synchronized with the microwave. Overall, the input reflection of the receiver cable within the two groups WLAN IEEE 802.11a (5.15-5.35 GHz and 5.725-5.825 GHz) is 10 dB, therefore the connection between the 2 radio cables of the 2 groups of radio cables is 20 dB.

Guo Yuanyuan. *et al.*<sup>[4]</sup> provides this text and is investigating another open backbone link for broadband exchange (UWB). The radiation is just printed on one side on a suitable substrate with a thickness of 1.6 mm FR 4, which may easily be tailored to different substrates. thanks to the reduction of innovations and therefore the development of knowledge trans- mission capacity, the proposed radio wire features a minimum size of 36mm 36mm including the substrate. additionally, the quality receiving cable was developed and tested and offers three 0.25-10.7 GHz with acceptable triangular generation compatibility.

Partha kumar Deb. *et al.*<sup>[5]</sup> Microwave correspondence frames require excellent radio wiring performance for a few times. A wireless cable should be connected to multiple

receiver cables to scale back equipment and construction costs. Additionally, unlike the previous dual-band design, this configuration swapped the receiver cable, creating VSWR and gain. HFSS 13.0 is employed for display and research. Although the proposed configuration is meant for dual-band activity, the simulation results show two resonance frequencies: 4.8 GHz, 6 GHz within the C-band, and 9.2 GHz within the X-band, which is more interesting than previous work. Harish Rajagopalan *et al* [6] this text presents an E-shaped broadband receiver wire arrangement using particle swarm simplification. Ideal keys are wont to show evidence of the thought of redoing the reconfiguration. If the sound performance is sweet, you get an extended program that works within the frequency range from 2 GHz to three .25 Hz (53 absolute data transmission). A ranking model and estimates are made.

Harish Rajagopalan *et al* [6] Microstrip Fix radio cables are generally utilized in top quality applications thanks to their low weight, comparability and straightforward and medium verification. These same rooms for radio cable repair consist in opening the modified structure of the E-receiver cable and therefore the U-patch radio cable. This receiver cable provides a transmission repair speed of roughly 16.4 with 1.5 VSWR. The recovery reaction was administered with the High Frequency Structure Testing System (HFSS). The properties of the receiver line like data transmission capacity, S-Limit and VSWR are examined. This document is additionally seen between the change in funding strategies.

Sharat Kumar AJ. *et al* [7] With the arrival of innovations, the quantity of knowledge sent by correspondence frames has increased repeatedly over. The UWB wireless cabling shouldn't cause undesirable distortion, therefore the actual application is vital. this text reviews what has been discovered

thus far round the world and attempts to supply a summary of the situation of the scan within the UWB wireless cabling scheme.

## DESIGN METHODOLOGY

The processor assumes that the required records consist of the dielectric consistent of the substrate, resonant frequency  $f_r$  in Hz and consequently the height of the substrate  $h$  specify,  $f_r$  (Hz) and  $h$ .

The rectangular microstrip patch antenna has been designed by calculating the has been designed by calculating the length and width from the given equation

$$W = \frac{c}{2f \sqrt{\frac{(\epsilon_r + 10)}{2}}} \quad (1)$$

$$\epsilon_r f f = \frac{(\epsilon_r + 1)}{2} + \frac{(\epsilon_r - 1)}{2} \left[ 1 + 10 \frac{h}{W} \right]^{\frac{1}{2}} \quad (2)$$

$$\frac{\Delta_l}{h} = 0.412 \frac{(\epsilon_r f f + 0.300) \left[ \frac{W}{h} + 0.262 \right]}{(\epsilon_r f f - 0.258) \left[ \frac{W}{h} + 0.813 \right]} \quad (3)$$

$$L = \frac{c}{2f \sqrt{\epsilon_r f f}} - 2\Delta l \quad (4)$$

where  $c$  is the velocity of the light,  $\epsilon_r$  is the dielectric constant of substrate,  $f$  is the antenna working frequency,  $W$  is the patch 3D view of proposed E-shaped antenna & Design Geometry of E-shaped microstrip patch antenna.

## SIMULATION RESULTS

### Axial Ratio Vs Frequency

The axial quantitative relation is outlined because of the ratio between the minor and axis of the polarization oval. Recall that if the ellipse has a linear unit equal to the minor and major axis it transforms into a circle, and that we say that the antenna is circularly polarized. therein case the axial ratio is adequate unity (or zero decibels). Figure 3 represents Axial quantitative relation below 0 dB for 5.65GHz

### Conjugate Matching Factor Vs Frequency

Conjugate matching is likewise referred to as complicated conjugate matching or most electricity switch matching. In the presence of reactive components, most electricity is transferred to load whilst the burden resistance and supply resistance are the same and the burden reactance is the bad of the supply reactance. The determine Figure 4 represents Conjugate Matching Factor For the frequency zero GHz the Conjugate Matching Factor is -forty-five dB, for the frequency four. 6 GHz the Conjugate Matching Factor is zero dB and for the frequency five GHz the Conjugate Matching Factor is -five dB




Figure 3: Axial Ratio








Figure 8: Current Distribution




Figure 9: VSWR

### Current Distribution

Conjugate matching is also known as most electricity switch matching or difficult conjugate matching. When reactive components are present, the majority of electricity is transported to the load, even when the burden and supply resistances are equal, and the burden reactance is the worst of the supply reactance. Figure 8 represents the Current Distribution. The number four stands for Matching Factor for Conjugates Conjugate Matching Factor is -45 dB at zero GHz, zero dB at 4.66 GHz, and -five dB at 5.55 GHz.

### VSWR

VSWR (Voltage Standing Wave Ratio), is a proportion of how proficiently radio-recurrence power is sent from a force source, through a transmission line, into a heap (for instance,




Figure 10: Impedance of Antenna




Figure 11: Radiation Pattern

from a force intensifier through a transmission line, to an antenna). Figure 9 addresses VSWR for the recurrence 4.6 GHz the VSWR is 1.2

### Impedance of Antenna

Impedance relates the voltage and current at the contribution to the receiving wire. The genuine piece of the receiving wire impedance addresses power that is either emanated away or consumed inside the radio wire. The non-existent piece of the impedance addresses power that is put away in the close field of the receiving wire. Figure 10 addresses impedance of radio wire for the recurrence of 1.6 GHz is 2.5ohm.

### Radiation Pattern

The term radiation pattern (or antenna pattern or far-field pattern) refers to the directional (angular) dependence of the



strength of radio waves from an antenna or other source in the field of antenna design. Figure 11 shows the maximum gain of -156.35 dB.

## CONCLUSION

In this paper, an E-molded microstrip fix receiving wire utilizing IE3D software the plan of E-Shape Micro strip fix radio wires are broadly utilized in satellite, radar and remote correspondence. In this field are plan receiving wire is light weight, reduced size, and simple of assembling. The E-Shape microstrip fix receiving wire is plan for ultra-wideband recurrence. The ideal aftereffects of proposed receiving wire reproduce and tried in IE3D test system. The mimicked aftereffects of IE3D reproduction. The proposed receiving wire is arranged using a polyimide substrate with a substrate height of 1.6 mm. Pivotal proportion is under 0 dB. For the recurrence zero GHz the Conjugate Matching Factor is - 45 dB, for the recurrence four.6 GHz the Conjugate Matching Factor is zero dB and for the recurrence five GHz the Conjugate Matching Factor is - five Db. For the recurrence of 4.6 GHz with a return loss of - 24dB. The smith graph of E Patch Antenna is  $5.253+j55\Omega$ , the radiation proficiency at the recurrence 5.65GHz is 88%. The Antenna Efficiency for the recurrence 4.5 GHz is 80%.

## REFERENCES

- [1] Hsiao, F.R. and Wong, okay.L. (2002) .compact flat inverted F patch antenna for tri-band operation, microwave alternative generation charter.
- [2] Yuehe Ge, Member, IEEE, Karu P. Esselle, (2004) Senior Member, IEEE, and Trevor S. Bird, Fellow, IEEE Shaped Patch Antennas for High-Speed Wireless Networks IEEE TRANSACTIONS ON ANTENNAS AND PROPAGATION, VOL. 52, NO. 12, DECEMBER.
- [3] Ahmed, O. M. H. additionally, A. R. Sebak (2009), "An epic maple-leaf molded UWB recieving wire with a 5.0–6.0 GHz band-indent brand," Progress In Electromagnetics Research C, Vol. 11, 39–49.
- [4] Pei Cheng Ooi and Krishnasamy T. Selvan (2009) "More modest T-Shaped CPW-Fed Printed Antenna for 3.5 GHz WiMAX Applications" 978-1- 4244-4076- 4/09/\$25.00 IEEE.
- [5] Rashmi Gyawali, Praveen Kumar Penta, V.Sudha (2011) "CPW-FED S-Shaped Single Band WLAN Antenna" PROCEEDINGS OF ICETECT.
- [6] Satya Kumar. V ,Anup Kumar Gogoi (2011) "Plan of T-Shaped Slot Antenna for UWB Communications Systems" International Conference on Broadband Furthermore, Wireless Computing, Communication and Applications.
- [7] Tang, M.C., S xiao., D. Guan, B. Wang, G.De (2011), "traditionalist UWB wireless wire with different band scores for WiMax and WLAN", too, IEEE Transactions on antennas, spread, vol. 59, no. 4, 1372-1376, April.
- [8] Two-time band score Wire reception with the UWB parasitic strip, "Progress of the Electromagnetic Research Letter", "Vol. 25, 21-30, 2011". Z. Yin.
- [9] Yuanyuan Guo, Xiaomiao Zhang, Yang Luo (2011), Pu Wan National Key Laboratory of Science and Technology on Antennas and Microwaves Xidian University "An inverted E-shape antenna for UWB applications" 978-1-4244-8268-9/11/\$26.00 IEEE.
- [10] Harish Rajagopalan, Joshua Kovitz, and Yahya Rahmat (2012) Samii Electrical Engineering Department University of California, Los Angeles Los Angeles, California, USA Frequency Reconfigurable Wideband E-shaped Patch Antenna: Design, Optimization, and Measurements 978-1-4673-0462-7/12/\$31.00 IEEE.
- [11] J. Xu, D. Shen, X. Zhang, and K. Xu, J. Xu, D. Shen, X. Zhang, and K. Xu (2012), J IEEE Antennas and Propagation Society, "A diminished plate ultrawideband (UWB) radio wire with quintuple band dismissals," Wireless Proliferation Letters, Vol. XI of November, 1517–1520.
- [12] Jiang, W. additionally, W. Che (2012), "An epic UWB radio wire with twofold scored packs for WiMAX and WLAN applications," IEEE Antennas and Wireless Spread Letters, Vol. 11, 293–296.
- [13] Zhu, Wu (2013) "A dwindled quad band-scored UWB monopole radio cord stacked one equal L-fashioned space," Progress in Electromagnetics Research, Vol. 139, 303–315, 2013. H.F. Wei, X. W. Shi, and W. T. Li, "A dwindled quad band-scored UWB monopole radio cord stacked one equal L-f fashioned space," Progress In Electromagnetics Research, Vol. 139, 303–315.
- [14] "Reconfigurable UWB radio wire with RF-MEMS for on-demand WLAN excusal," IEEE Exchanges on Antennas and Propagation, Vol. 62, No. 2, 602– 608, February . D. E. Anagnostou, M. T. Chrysomallis, B. D. Braaten, J. L. Ebel, and N. Sep'ulveda (2014), "Reconfigurable UWB radio wire with RF.
- [15] IEEE Antennas and Far-off Propagation Letters, Vol. 13, 396–399. "A diminished microstrip-oversaw triple band-scored UWB monopole radio Cable," IEEE Antennas and Far-off Propagation Letters, Vol. 13, 396–399, 2014. D. Sarkar, K. V. Srivastava, and K. Saurav. D. Sarkar, K. V. Srivastava, and K. Saurav, (2014).
- [16] The summarized thought for band score age in genuinely wide band radio wires," Progress In Electromagnetics Investigation C, Vol. 54, 179–185, 2014.
- [17] Partha kumar Deb, Tamasi Moyra and Priyansha Bhowmik (2015). Department of Electronics and Communication Engineering, National Institute of Technology, Agartala- 799046, West Tripura, India International Conference on Signal Processing and Integrated Networks (SPIN).
- [18] Mishra, G., and S. Sahu (2016), "Restricted indirect fix UWB receiving wire with WLAN band score ascribes," Microwave and Optical Technology Letters, Vol. 58, No. 5, May, 1068–1073..
- [19] Innovative technology confirms the distorted design of microfilter receivers for ultra-wideband applications." "Journal of Microwave and Electromagnetic Applications," Volume 16, Issue 3, 765-776, September . Zehforoosh, Y. Men (2017).
- [20] J.Jasika Fairy, M.Nesasudha (2017) "Low Profile recieving wire plan for biomedical applications" International Conference on Signal Processing and Correspondence "(ICSPC'17) – 28th and 29th July.
- [21] J.Jasika Fairy, M.Nesasudha (2017) "Low Profile recieving wire plan for biomedical applications" International Conference on Signal Processing and Correspondence "(ICSPC'17) – 28th and 29th July.
- [22] Mewara, HS, D. Jhanwar, MM Sharma and JK Deegwal (2017), "Storyline Hammer UWB receiver cable with three-slot strap for RLS, WLAN and XSCS Components", "Advanced Electromagnetics", Vol. 1.6, Issue 4, pages 36-41, October.
- [23] Sharath Kumar A J, T P Surekha (2017) "Antennas for Ultra-Wide Band Communication Applications: A Survey" International Conference on Current Trends in Computer, Electrical, Electronics and Communication (ICCTCEEC-2017).

- [24] Xi, L., H. Zhai, Y. Zang, and L. Li(2017), "A story two fold band tunable bandindented recieving wire," Microwave additionally, Optical Technology Letters, Vol. 59, 3014–3018.
- [25] Kundu, S(2018)., "Inflatable outlined CPW managed printed UWB radio wire with twofold recurrent indent to butcher WiMAX and WLAN obstructions,"Microwave and Optical Technology Letters, Vol. 60, 1744–1750.
- [26] Mewara (H.I.) S., J.K. Deegwal and PM Sharma(2018), "Early Resonator Based on Fourth Band, Box Band, Unipolar,Ultra Wideband Line Attenuation". 83,470-478.
- [27] Rahman, art. , Q. Cao(2018), and. You're about to Jill (W Yi, "Plan three UWB relies on circular sound to restore flex", International Radio Frequency and Microwave Computer Data Engineering, E21648, 2018, E21648.
- [28] Elhabchi, M., M. N. Siri and R. Touahni(2019), "Wireless Airplane Definition ' UWB" with miniatized isosceles with SPW-Dially Spased SCASED Credit, Advances in Electromagnetic Research Taper, Vol. 87.59-66.
- [29] QADDI Mohamed Hamza, SRIFI Mohamed Nabil and MHARZI Hassan(2019) Microstrip Patch Antenna for Ultra-Wideband Applications Advances in Science, Technology and Engineering Systems Journal Vol. 4, No. 3,10-15.
- [30] Ros Marie C Cleetus , G. Josemin Bala(2019) " Design and Analysis of a Frequency Reconfigurable Antenna for Ultra-wide band and Cognitive Radio Applications" 2019 International Conference on Signal Processing and Communication (ICSPPC -2019), March. 29 – 30, 2019, Coimbatore, INDIA .
- [31] N. Jaglan, B. K. Kanaujia, S. D. Gupta, S. Srivastava "Band notched UWB circular monopole antenna with inductance enhanced modified mushroom EBG structures" Wireless Netw DOI 10.1007/s11276-016-1343-7.

